## **145** Preference<sup>®</sup>



## **145 Preference®**

| D                       |         | D. I.C. I. D.C.   | PRODUCT SPECIFICATIONS                        |   |
|-------------------------|---------|---|---|---|
| Designation             |         | Dust Control Matting  |   |   |
| Description             |         | Absorbent /scrape carpet mat  |   |   |
| Material                | 1       |   |   |   |
|                         | Тор     | Loop pile carpet of tou<br>chessboard design.<br>900 grams of dual yar  |   | and soft Decalon® yarns, tufted in attractive         |
|                         | Backing | Vinyl   |   |   |
| Process                 |         | Tufted  |   |   |
| Category                |         | Indoor absorbent - Elegance   |   |   |
| Recommended use         |         | Indoor - medium to heavy traffic  |   |   |
| Colours                 |         | Charcoal, Red, Burgundy, Brown, Green, Navy Blue  |   |   |
| Weight                  |         | 4 kg/m <sup>2</sup>   |   |   |
| Thickness               |         | 8 mm  |   |   |
| Standard sizes          |         | 60 cm x 90 cm<br>90 cm x 120 cm<br>90 cm x 150 cm<br>120 cm x 180 cm<br>120 cm x 240 cm<br>120 cm x 18.3 m<br>180 cm x 18.3 m   |   |   |
| Custom sizes            |         | 120 cm and 180 cm per linear meter  |   |   |
| Special rer             |         |   |   |   |
| -                       |         |   | PRODUCT TESTING                               |   |
| Tests                   |         |   | Norms   | Results   |
| Abrasion resistance     |         |   | ASTM D3884                                    | 4.2% weight loss                                      |
| Colour fastness to ligh |         | nt  | AATCC 16E                                     |   |
| Accelerated wear test   |         | by sim floor machine  | U.S.  | 2   |
| Accelerated soiling     |         |   | ASTM D6540                                    | 4,5   |
| Anti-slip               |         |   | DIN51130 - BGR181                             |   |
| Water retention         |         |   | ISO 4920 TNO W6034                            | 3.6 l/m <sup>2</sup>                                  |
| Sanitary epidemiologi   |         | c test  | GN 2.1.6.1338-03 MCL<br>GN 2.1.6.2309-07 OBUV | Pass - Certificate no.<br>77.01.16.229.P.044984.07.09 |
| Breaking l              | oad     |   | ASTM D412                                     | 53,7 lb   |
| Elongation              |         |   | ASTM D412                                     | 30,4%   |
|                         |         |   | FIRE TESTING                                  |   |
|                         |         | Surface Flammability  | ASTM D2859                                    | Pass  |
|                         |         | Classification of the<br>reaction to fire<br>performance  | DIN EN 13501-1                                |   |
| Sustainability          |         | <ul> <li>Recyclable material</li> <li>REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals)</li> <li>Contributes to cleaner environment by reducing need of cleaning chemicals</li> </ul> |   |   |



• Free of toxic DOP and DMF.

www.notrax.eu